

The Shield *Pilecki* Timepiece

(SH0601 – SH0608)



Setting Instructions

- 1) Unscrew the crown by rotating it counterclockwise until it is free from the case threads.
- 2) Pull the crown out two clicks to its outermost position.
- 3) Rotate the crown counterclockwise until the date indicator advances one position.
- 4) Set the current time as follows:
 - for AM hours advance the hands directly to the current time,
 - for PM hours advance the hour hand one full rotation (12 hours) *once*, prior to setting the time.
- 5) Push the crown in one click to its middle position.
- 6) Set the current date by rotating the crown clockwise until the correct value is displayed.
- 7) Push the crown in to its innermost rest position to commence timekeeping.
- 8) Secure the crown to the case by pressing in on the crown and carefully starting the threads by rotating the crown clockwise. Screw the crown down until it is fully seated – *finger tighten only*.

Note: Setting the time to AM / PM accordingly ensures that the date indicator changes at midnight rather than noon. If the date indicator is changing in the afternoon advance the hour hand one full rotation (12 hours), then reset the date indicator as necessary.

Water Resistance Guidelines

50 ATM – Approved for bathing, swimming, and diving. **Note:** the crown must be properly secured to the case to achieve the rated water resistance. Additionally, manipulation of the crown while the watch is in contact with water will negate the rated water resistance as water penetration may occur.